

ABC FIRE EXTINGUISHER Model: HY- 0601



Capacity	1kg	2kg	3kg	4kg	6kg	9kg
Fire rating	5A/55B	13A/55B	13A/55B	21A/144B	34A/233B	43A/233B
Working pressure	14kgf/cm2					
Test presure	25kgf/cm2					
Overall height (mm)	313	445	460	473	503	610
Diameter (mm)	85	98	115	139	181	181
Width(mm)	90	100	110	185	232	232
Empty weight	1.01	1.60	1.97	2.43	3.39	4.01
Full weight	2.01	3.60	4.97	6.43	9.39	13.01
Min. discharge time (s)	6.1	6.9	11.7	15.0	16.0	17.0
W. temperature	20°C to 60°C					
Safe operating distance	2 meters					

CO2 FIRE EXTINGUISHER Model: HY- 0602



Capacity	3kg	5kg
Fire rating	34B	55B
Working pressure	60kgf/cm2	
Test presure	250kgf/cm2	
Overall height (mm)	600	650
Diameter (mm)	114	152
Width(mm)	158	175
Empty weight	8.7	12.07
Full weight	12.6	17.60
Min. discharge time (s)	9.4	13.1
W. temperature	20°C to 60°C	
Safe operating distance	2 meters	

AUTOMATIC FIRE EXTINGUISHER Model: HY- 0603



Capacity	6kg	9kg	12kg
Volume(L)	7.5	11.25	15
Diameter(mm)	φ292	φ314	φ334
Height(mm)	268	305	330
Cylinder weight (kg)	3.75	4.87	5.74
Full weight (kg)	9.94	14.1	17.93
Temperaturre range	-10°C ~ +60°C	-10°C ~ +60°C	-10°C ~ +60°C
Operating temperature	68°C	68°C	68°C
Working pressure @20oC	14 bar	14 bar	14 bar
Test pressure	25 bar	25 bar	25 bar
Cylinder material	CS HP295	CS HP295	CS HP295
Norminal carton size (mm)	300x300x290	325x325x325	345x345x350



Authorized by: **SHANGYU HONGYE FIRE PROTECTION EQUIPMENT FACTORY**

Adress: WUSHAN VILLAGE, XIAOYUE TOWN, SHANGYU, ZHEJIANG, CHINA

Tel: 0086-574-62758988

Fax: 0086-574-22689688